

GEHRIG Ariane GTW 3300 dishwasher

**SWISS
MADE**

Product details

- Undercounter dishwasher for glasses, crockery and cutlery
- Suitable for 500 x 500 mm dishwasher racks
- Ample loading height of 425 mm
- Space-saving width of 550 mm
- Extremely simple operation using rotary pushbutton, text and status display
- Sturdy chrome-nickel steel tank, frame, tank filter, wash and rinse arms and panelling
- Double-walled, insulated door
- Illuminated washing chamber
- Patented rotation monitoring of the wash and rinse arms
- 4-stage filter system
- Dirt caught in the filter screen is pumped out after every wash cycle
- Integrated dosing devices for dishwashing detergent and shine and rinse aid
- 8 factory-set programmes
- Steam rinse cycle for low water consumption: 1.7 l/rack
- Programmes are configured and can be adapted within specified limits
- Perfect dishwashing results with AQUALYT detergent
- Rounded corners in one-piece wash tank for easy cleaning
- 4 languages
- Gateway for real-time machine data via IoT platform GG+connect

Options

- Hygiene programme for thermal disinfection
- 2nd rack level for simultaneous washing of 2 loaded racks
- Extensive range of GEHRIG dishwasher racks
- Conductivity sensor
- Panel for 60 cm recess

Features and benefits

- Every wash programme produces impeccable wash results in the blink of an eye
- Low operating costs thanks to low water and energy consumption values
Performance values in accordance with EN IEC 63136 – see product data sheet
- Hygiene programme for the most stringent cleanliness requirements achieves excellent levels of disinfection in just a few minutes (optional)
- Sturdy and reliable, Swiss high-quality product
- GG+connect provides an overview of the machine fleet and machine statuses any time and from anywhere
- Digital access to HACCP data with one-click PDF download
- Faults and misuse are detected and reported by email, text message or push notification.
The desired delivery method can be customised and configured for every user using GG+connect.
- Automatic detergent replenishment; GG+connect determines the optimum reordering schedule and replenishes reserves in good time based on consumption values.

Technical data

Product line		Ariane GTW 3300			
Model variant		GTW 3300 - 55	GTW 3300 - 60	GTW 3300-H - 55	GTW 3300-H - 60
Product number		1041521-55	1041521-60	1072096-55	1072096-60
Technical properties					
Theoretical rack throughput	Racks/h	40			
Water consumption	l/rack	1.9 / 1.7 steam rinse			
Cycles times	s	90 / 150 plus special programmes			
Dimensions					
Size (WxHxD)	mm	549 x 850 (885) x 597	599 x 850 (885) x 597	549 x 850 (885) x 597	599 x 850 (885) x 597
Loading height	mm	415			
Rack size (including racks with high sides)	mm	500 x 500			
Tank capacity	l	13			
Weight	kg	67			
Electrical parameters					
Voltage	V	400 3N~ 50Hz 230 1N~ 50Hz			
Rated power	kW	9.1			
Fuse protection	A	16 / 16			
Tank heater	kW	2.5			
Boiler heater	kW	5.5			
Pump power	kW	0.5			
Ambient conditions					
Emission sound pressure level L _{pA}	dB (A)	56 ¹			
Water supply					
On-site water pressure	MPa	0.1 - 1			

¹Measurement uncertainty $K_{pA} = 2.5$ dB

